



MQS

TE Internal #: 1-968720-2
Horizontal, Wire-to-Board, 32 Position, 2 Rows, 2.54mm [.1in]
Centerline, Tin (Sn), Printed Circuit Board, Signal, Black, Panel
Mount
[View on TE.com >](#)

Automotive Parts > Automotive Connectors > Automotive Headers > Signal Header



PCB Mount Orientation: **Horizontal**
Connector System: **Wire-to-Board**
Number of Positions: **32**
Number of Rows: **2**
Centerline (Pitch): **2.54 mm [.1 in]**

[All Signal Header \(240\)](#)

Features

Product Type Features

Connector Product Type	Connector Assembly
Mixed & Hybrid Header	No
Header Type	Fully Shrouded
Connector Shape	Rectangular
Connector System	Wire-to-Board
Sealable	No
Connector & Contact Terminates To	Printed Circuit Board

Configuration Features

Number of Signal Positions	32
Number of Sections	1
PCB Mount Orientation	Horizontal
Number of Positions	32
Number of Rows	2



Electrical Characteristics

Operating Voltage	12 VDC
Nominal Voltage Architecture	12 V

Body Features

Connector & Keying Code	A
Primary Product Color	Black

Contact Features

Mating Tab Width	.63 mm[.025 in]
Mating Tab Thickness	.63 mm[.025 in]
Contact Type	Tab
Contact Mating Area Plating Material	Tin (Sn)

Termination Features

Termination Method to PCB	Through Hole - Solder
---------------------------	-----------------------

Mechanical Attachment

Panel Mount Feature	With
Mating Retention Type	Locking Interface
PCB Mount Retention	With
Mounting Holes	With
PCB Mount Retention Type	Mounting Hole
Mating Alignment	With
PCB Mount Alignment	With
Connector Mounting Type	Panel Mount

Housing Features

Centerline (Pitch)	2.54 mm[.1 in]
--------------------	----------------

Dimensions

Connector Width	28.4 mm[1.118 in]
PCB Thickness (Recommended)	.8 – 1.6 mm[.031 – .063 in]
Profile Height from PCB	17 mm[.669 in]
Connector Length	55.86 mm[2.199 in]

Usage Conditions

Operating Temperature (Max)	125 °C[212 °F]
-----------------------------	----------------



Operating Temperature Range

-40 – 130 °C[-40 – 266 °F]

Operation/Application

Shielded	No
Circuit Application	Signal

Packaging Features

Packaging Quantity	256
Packaging Method	Tray

Other

Interface Number	114-18063-032
------------------	---------------

Product Compliance

For compliance documentation, visit the product page on [TE.com](#)>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JAN 2025 (247) Candidate List Declared Against: JAN 2025 (247) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Not applicable for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: <https://echa.europa.eu/guidance-documents/guidance-on-reach>

Compatible Parts



TE Part # 1-968719-2
[MQS PINHEADER 32POS.](#)

TE Part # 2-967348-2
[MQS SHIELD FOR HOUSING 32POS.](#)

Customers Also Bought

TE Part #54489-4
[HSG ASSY,PWR LK,SRS1,4POS,FLNG](#)

TE Part #735212-1
[FF 250 REC 22-17AWG BR](#)

TE Part #CAT-SIGH262
[Signal Header](#)

TE Part #3-1462039-1
[IM26GR=IM RELAY 50mW 12V](#)

TE Part #2302451-1
[MATENET, MALE INSERT MODUL](#)

TE Part #1-967162-2
[3pos MQS .63 header 90deg THR](#)

TE Part #7-1904107-4
[V23201-R1001-A512](#)

TE Part #2298721-1
[4P,MATE-AX,SOC HSG ASSY,180DEG, COD A](#)

TE Part #1-2840575-1
[PCON12,TERMINAL,FAM SLD/UNSLD](#)

Documents

Product Drawings

[32pos MQS .63 header 90deg THR](#)

English

CAD Files

[3D PDF](#)

3D

Customer View Model

[ENG_CVM_CVM_1-968720-2_B1.2d_dxf.zip](#)



English

Customer View Model

[ENG_CVM_CVM_1-968720-2_B1.3d_igs.zip](#)

English

Customer View Model

[ENG_CVM_CVM_1-968720-2_B1.3d_stp.zip](#)

English

By downloading the CAD file I accept and agree to the [Terms and Conditions](#) of use.

Product Specifications

Application Specification

English