

DATASHEET - FUSE 1000A 1000V 3TN/110 AR UR



Fuse-link, high speed, 1000 A, AC 1000 V, 125 kA, DIN 3, 74 x 90 x 139 mm, aR, DIN, IEC, type T indicator



Part no. FUSE 1000A 1000V 3TN/110 AR UR
Catalog No. 170M8639

Delivery program

Product range			Fuse
Basic function			Fuse-link
Field of application			high speed
Rated current	I	A	1000
Rated voltage			AC 1000 V
Construction size			DIN 3
Size			74 x 90 x 139 mm
Utilization category			aR
Status indicator			type T indicator
Breaking Capacity		kA	125
usable for size/applications			semiconductor protection
Standard/Approval			DIN IEC
Shape			square body with centre-bolted tags (slotted)
Standards/Regulations			DIN 43653 IEC 60269-4

Technical data ETIM 7.0

Circuit breakers and fuses (EG000020) / Low Voltage HRC fuse (EC000055)			
Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Low-Voltage HRC fuse (ecl@ss10.0.1-27-14-20-05 (AFZ800015))			
Construction size			Other
Rated current		A	1000
Rated voltage		V	1000
Voltage type			AC
Rated switching capacity		kA	125
Utilization category			aR (accompanied semiconductor protection)
Type of fuse status indicator			Top fuse status indicator
Insulated metal gripping lugs (IMGL)			No

Additional product information (links)

Product datasheet (pdf)	http://www.cooperindustries.com/content/dam/public/bussmann/Electrical/Resources/product-datasheets-b/Bus_Ele_DS_720061_Square_Body_DIN_43_656.pdf
-------------------------	---