



Fuse-link, high speed, 1250 A, AC 690 V, size 3, 76 x 76 x 150 mm, aR, IEC, single indicator



Part no. FUSE 1250A 690V 3SHT AR UC
Catalog No. 170M8547

Similar to illustration

Delivery program

Product range			Fuse
Basic function			Fuse-link
Field of application			high speed
Rated current	I	A	1250
Rated voltage			AC 690 V
Construction size			size 3
Size			76 x 76 x 150 mm
Utilization category			aR
Status indicator			single indicator
usable for size/applications			Protection of power rectifiers
Standard/Approval			IEC
Shape			square body with special bladed contacts
Standards/Regulations			IEC 60269-4

Technical data ETIM 7.0

Circuit breakers and fuses (EG000020) / Low Voltage HRC fuse (EC000055)			
Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Low-Voltage HRC fuse (ecI@ss10.0.1-27-14-20-05 [AFZ800015])			
Construction size			Other
Rated current		A	1250
Rated voltage		V	690
Voltage type			AC
Rated switching capacity		kA	200
Utilization category			aR (accompanied semiconductor protection)
Type of fuse status indicator			Other
Insulated metal gripping lugs (IMGL)			No