

Product data sheet

Specifications



QO mini breaker, 125 A, 3 pole, 120/240 V, 22 kA, bolt on

QOB3125VH

 **Discontinued on:** Jan 7, 2025

 **Discontinued**

Main

Product	Miniature circuit-breaker
Range	QO
Current Rating	125 A
Voltage Rating	120/240 V AC 240 V AC 120 V AC
Mounting Type	Bolt-on
Number of Poles	3P
Circuit Breaker Type	Standard
Ratings	Not rated
Electrical Connection	Box lugs

Complementary

Interrupt Rating	22 kA at 120/240 V AC 22 kA at 240 V AC 22 kA at 120 V AC
Number of Panel Spaces	6
Wire Size	AWG 4...300 kcmil copper or aluminium
Tightening Torque	5.6 N.m
Height	145 mm
Width	114 mm
Depth	124 mm
Net weight	0.435 kg

Environment

Certifications	UL listed CSA
Ambient Rating	40 °C

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	10.922 cm

List Price displayed is VAT EXCLUSIVE.

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Package 1 Width	12.700 cm
Package 1 Length	17.272 cm
Package 1 Weight	1.769 kg
Unit Type of Package 2	PAL
Number of Units in Package 2	558
Package 2 Height	101.600 cm
Package 2 Width	101.600 cm
Package 2 Length	121.920 cm
Package 2 Weight	1005.160 kg

Contractual warranty

Warranty (in months)	18
----------------------	----

Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

 Environmental footprint	
Total lifecycle Carbon footprint	28
Environmental Disclosure	Product Environmental Profile

Use Better

 Materials and Substances	
Packaging made with recycled cardboard	No
Packaging without single use plastic	Yes
EU RoHS Directive	Compliant
SCIP Number	Af42fb01-813d-40c0-ae28-b8b3299dbc99
REACH Regulation	REACH Declaration
Halogen-free status	Halogen free product

Use Again

 Repack and remanufacture	
End of life manual availability	No need of specific recycling operations
Take-back	No