

Specifications



Photo is representative



Eaton BK/S500-2-R

Eaton S500 Series Fast-acting fuse 2A, 250 Vac or less, 32 Vdc (self certified), BK-S500-2-R

General specifications

PRODUCT NAME	Eaton Bussmann series S500 fast-acting fuse
CATALOG NUMBER	BK/S500-2-R
UPC	051712643399
PRODUCT HEIGHT	20.5 mm
PRODUCT DIAMETER	5.2 mm
PRODUCT WEIGHT	0.7 g
WARRANTY	Not Applicable
COMPLIANCES	CCC Marked CE Marked RoHS Compliant
CERTIFICATIONS	VDE
GLOBAL CATALOG	BK/S500-2-R



Powering Business Worldwide

Product specifications

AMPERAGE RATING	2 A
FREQUENCY RATING - MAX	50 Hz
FREQUENCY RATING - MIN	50 Hz
VOLTAGE DROP	150 mV maximum
INTERRUPT RATING	35 AIC at 250 Vac
FUSE INDICATOR	Non-indicating
CONNECTION	Ferrule end x ferrule end
MATERIAL	Glass tube Nickel-plated end-cap construction
QUANTITY	100
VOLTAGE RATING	250 Vac or less, 32 Vdc (self certified)
TYPE	Electronic
APPLICATION	Electronic circuits

Resources

SPECIFICATIONS AND DATASHEETS

[Eaton S500 glass tube fuses data sheet](#)

[Eaton Specification Sheet - BK/S500-2-R](#)

PROJECT NAME:

PROJECT NUMBER:

PREPARED BY:

DATE:



Eaton Corporation plc

Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2025 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.

