



Fuse-link, low voltage, 20 A, AC 550 V, BS88/A1, 14 x 55 mm, gL/gG, BS



Catalog No. 20SF21

## Delivery program

|                              |   |    |                                 |
|------------------------------|---|----|---------------------------------|
| Product range                |   |    | Fuse                            |
| Basic function               |   |    | Fuse-link                       |
| Field of application         |   |    | low voltage                     |
| Rated current                | I | A  | 20                              |
| Rated voltage                |   |    | AC 550 V                        |
| Construction size            |   |    | BS88/A1                         |
| Size                         |   |    | 14 x 55 mm                      |
| Utilization category         |   |    | gL/gG                           |
| Description                  |   |    | Sealed version of NITD20        |
| Breaking Capacity            |   | kA | 80                              |
| usable for size/applications |   |    | general industrial applications |
| Standard/Approval            |   |    | BS                              |
| Shape                        |   |    | offset bolted tags (slotted)    |
| Standards/Regulations        |   |    | BS88-2<br>IEC 60269-2           |

## Technical data ETIM 7.0

|                                                                                                                                                                                     |  |    |                                               |
|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--|----|-----------------------------------------------|
| Circuit breakers and fuses (EG000020) / Low Voltage HRC fuse (EC000055)                                                                                                             |  |    |                                               |
| Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Low-Voltage HRC fuse (ecl@ss10.0.1-27-14-20-05 [AFZ800015]) |  |    |                                               |
| Construction size                                                                                                                                                                   |  |    | Other                                         |
| Rated current                                                                                                                                                                       |  | A  | 20                                            |
| Rated voltage                                                                                                                                                                       |  | V  | 550                                           |
| Voltage type                                                                                                                                                                        |  |    | AC                                            |
| Rated switching capacity                                                                                                                                                            |  | kA | 80                                            |
| Utilization category                                                                                                                                                                |  |    | gL/gG (cable protection/equipment protection) |
| Type of fuse status indicator                                                                                                                                                       |  |    | None                                          |
| Insulated metal gripping lugs (IMGL)                                                                                                                                                |  |    | No                                            |